

TITLE OF THE INVENTION

LAMINATED COMPOSITE, INFORMATION RECORDING MEDIUM, AND
MEMBER OF IMPARTING FORGERY-PREVENTING CHARACTERISTIC

CROSS-REFERENCE TO RELATED APPLICATIONS

5 This is a Continuation Application of PCT
Application No. PCT/JP00/03292, filed May 23, 2000,
which was not published under PCT Article 21(2) in
English.

10 This application is based upon and claims the
benefit of priority from the prior Japanese Patent
Application No. 11-143998, filed May 24, 1999, the
entire contents of which are incorporated herein by
reference.

BACKGROUND OF THE INVENTION

15 1. Field of the Invention

 The present invention relates to a laminated
composite, an information recording medium, and
a member of imparting a forgery-preventing
characteristic, and more particularly, to a laminated
20 composite which can be used in discriminating
an information recording medium between genuine one and
a counterfeit by using a latent image, an information
recording medium which can be discriminated between
a genuine one and a counterfeit by using the latent
25 image, a member of imparting, to an information
recording medium, a forgery-preventing characteristic
which enable discrimination of the information

recording medium between a genuine one and a counterfeit.

2. Description of the Related Art

Conventionally, as techniques for preventing
5 forgery of information recording mediums such as credit cards, securities, and certificates, methods using a latent image are known. The methods employ, for example,

1) A picture drawn by parallel lines: a latent
10 image such as a hidden letter is drawn in a space between the parallel lines and the latent image can be visualized by concealing the parallel lines, and

2) A decomat: a latent image is formed by
a printing technique using a transparent ink medium
15 which contains a filler and the latent image can be visualized by rubbing the printed portion with a pencil so as to allow a powder from a lead of the pencil to attach onto the printed portion.

However, in methods 1) and 2), the latent image is
20 legible if carefully observed. Thus, these methods 1) and 2) are used for pleasure rather than as a practical forgery-preventing technique.

As a more practical forgery-preventing technique, the following methods are known:

25 3) A method in which a latent image is formed by use of an irreversible thermochromic ink which is white or colorless and transparent and develops a color by

application of heat.

4) A method in which a latent image is formed by a printing technique using a white ink which contains a filler such as titanium oxide harder than a metal, and the latent image can be visualized by rubbing the printed portion with a coin or the like.

However, the method 3) requires a heating device to visualize the latent image. In addition, once the latent image is visualized in the method 3), it cannot be returned to an invisible state. On the other hand, in the method 4), although the image such as a letter is rendered invisible by forming a mat-like varnish layer thereon, once the latent image is visualized, it cannot be returned to an invisible state. Therefore, the methods 3) and 4) can be used only once.

As a technique capable of repeating visualization and nonvisualization of a latent image, the following techniques are known.

5) A method in which a latent image is formed or a image is concealed by using a reversible thermochromic ink, which reversibly develops and loses a color thereof by application of heat and returns to its original state if left alone for a while.

6) A method in which a latent image is formed by using a photochromic ink, which is capable of developing a color by light irradiation, particularly, by ultraviolet irradiation, as the white or colorless

and transparent ink; and

7) A method in which a latent image is formed by using an organic type or an inorganic type of fluorescent ink, which is capable of developing a color by ultraviolet irradiation, as the white or colorless and transparent ink.

However, the thermochromic ink used in the method 5) has a problem that the resistance thereof, particularly, the heat resistance, is low. The photochromic ink used in the method 6) also has a problem that the resistance thereof, particularly, the light stability is low.

When an organic fluorescent ink is used in the method 7), sufficient luminescence can be obtained simply by adding an extremely small amount of organic phosphor to a printing ink. However, the organic phosphor is low in light stability. Furthermore, when an inorganic fluorescent ink is used in the method 7), a large amount of inorganic phosphor (about 10-20%) need be added to a printing ink in order to obtain sufficient luminescence. Due to this, the latent image formed by using the inorganic fluorescent ink is apt to be legible by visual observation. Thus, the design of the latent image must be carefully made.

As mentioned above, methods 5)-7) are limited in application because of the resistance of ink.

As a forgery-preventing technique capable of

repeating visualization and nonvisualization of the latent image, the following methods are known:

8) A method in which a latent image is formed by use of dots of a screen and moiré fringes of parallel lines. In this method, the latent image is formed by partly changing the pitch of the dots or the pitch and/or angle of the parallel lines. Thereafter, a transparent film having regularly arranged dots or parallel lines thereon is overlaid on the latent image to visualize the latent image.

According to the method 8), the latent image can be visualized simply by using the transparent film. Thus, the visualization and non-visualization of the latent image can be easily repeated. In addition, this method is free from the problem of resistance, so that application of the method is not limited. However, the method 8) has a problem that a complicated latent image cannot be obtained.

As another forgery-preventing method which can repeat the visualization and non-visualization of a latent image, the following method is known.

9) A method in which a latent image is formed by using a magnetic ink. In this method, a latent image is formed by partly magnetizing a magnetic layer which has a sufficiently high coercive force (about 300 Oe or more, or about 24 kA/m or more) enough to perform a magnetic recording, and the latent image is visualized

by sprinkling an iron powder over the magnetic layer. However, in this method 9), a latent image can be easily rewritten and forged. In addition, the step of visualizing the latent image is complicated and
5 requires a specific detection apparatus.

As another forgery-preventing technique which can repeat the visualization and nonvisualization of a latent image, the following method is known:

10 10) A method in which a latent image is formed by using an ink capable of absorbing infrared rays and a layer capable of transmitting the infrared rays and not transmitting visible light is formed on the latent image. However, this method requires an infrared camera etc. to visualize the latent image.
15 Accordingly, the method has a problem that the apparatus inevitably increases in size. Another method is also known using a white or colorless ink (IV ink) absorbing infrared rays and not absorbing visible light. However, this method also requires an infrared
20 camera etc.

According to the methods 9) and 10), it is possible to repeat the visualization and nonvisualization of a latent image and form a complicated latent image. In addition, there is no
25 limitation in application due to resistance of the latent image. However, the methods 9) and 10) require a specific apparatus to visualize the latent image, as

mentioned above.

BRIEF SUMMARY OF THE INVENTION

The conventional forgery-preventing techniques using a latent image have various problems as mentioned above.

5

An object of the present invention is to provide a forgery-preventing technique capable of repeating visualization and nonvisualization of a latent image, forming a complicated latent image having a sufficient resistance, easily discriminating an article between a genuine one and a counterfeit, and visualizing the latent image without using a large scale apparatus.

10

Another object of the present invention is to provide a laminated composite which can be employed in the forgery preventing technique, an information recording medium to which forgery-preventing characteristic is imparted by the forgery preventing technique, and a member of imparting the forgery-preventing characteristic to an information recording medium.

15

20

According to a first aspect of the present invention, there is provided a laminated composite comprising an optical layer having a light reflectivity, and a latent image formation layer containing a liquid crystalline polymer material and provided on one of major surfaces of the optical layer, wherein the latent image formation layer comprises at

25

least one oriented portion in an orientation state and at least one non-oriented portion in a non-orientation state, and the at least one oriented portion and the at least one non-oriented portion constitute a latent
5 image which is unrecognizable by a direct visual observation and recognizable by a visual observation through a polarizing member.

According to a second aspect of the present invention, there is provided an information recording
10 medium comprising a light reflective substrate with a light reflective surface, and a latent image formation layer containing a liquid crystalline polymer material and provided on the light reflective surface, wherein the latent image formation layer comprises at
15 least one oriented portion in an orientation state and at least one non-oriented portion in a non-orientation state, and the at least one oriented portion and the at least one non-oriented portion constitute a latent image which is unrecognizable by a direct visual
20 observation and recognizable by a visual observation through a polarizing member.

According to a third aspect of the present invention, there is provided a member of imparting forgery-preventing characteristic comprising a base
25 layer, an optical layer provided on one of major surfaces of the base layer and having a light reflectivity, and a latent image formation layer

containing a liquid crystalline polymer material and provided on the optical layer, wherein the latent image formation layer comprises at least one oriented portion in an orientation state and at least one non-oriented portion in a non-orientation state, and the at least one oriented portion and the at least one non-oriented portion constitute a latent image which is unrecognizable by a direct visual observation and recognizable by a visual observation through a polarizing member.

Note that, the term of "laminated composite" used herein includes all laminated structures formed by laminating a plurality of layers. The term "information recoding medium" used herein includes all mediums in which data are recorded. In particular, it refers to an information recording medium such as a credit card, a security and a certificate, which need to be discriminated between a genuine one and a counterfeit. Furthermore, the term "a member of imparting forgery-preventing characteristic" refers to a member of imparting forgery-preventing characteristic to the information recording medium and includes adhesive-backed sheets and self-adhesive seals (or self-adhesive stickers).

The phrase "be in an orientation state" refers to a state in which main chains or side chains of a polymeric liquid material, or both of them are

orientationally arranged in a single direction substantially parallel to the main surface of the latent image formation layer to the extent that a latent image can be fully recognized under visual observation through a polarizing member. Furthermore, the phrase "be in a nonorientation state" refers to a state in which the orientation degree of the main chain and side chain of the liquid crystalline polymer material is low or the liquid crystalline polymer material per se is not present. Therefore, under the nonorientation state, a latent image cannot be visually observed through a polarizing member.

As described in the above, a latent image-forming layer having the oriented portion and the non-oriented portion is combined with an optical layer or a light reflective substrate in the present invention. The oriented portion and non-oriented portion compose the latent image. Generally, they differ only in orientation state of the main chains or side chains of molecules of the liquid crystalline polymer material or both of them. The difference in orientation state between the first portion and the second portion cannot be distinguished by direct visual observation. However, if a polarizing member is used, the difference between them can be visually observed as difference in intensity of reflected light. In other words, since a relatively high contrast is produced between the

oriented portion and the non-oriented portion, the latent image can be easily recognized. In brief, the present invention enables discrimination of an article between a genuine one and a counterfeit without using
5 a large apparatus for visualizing a latent image.

In the present invention, the latent image can be visualized without changing the state of a latent image. Thus, the visualization and nonvisualization of the latent image can be repeated. Furthermore,
10 the latent image formation layer made of a liquid crystalline polymer material has a sufficient resistance.

The different orientation state mentioned above can be produced by extending a general polymer film such as a polypropylene film. However, such a film is
15 thick (usually 3 μm or more), so that the film is extremely limited in application range. In addition, it is extremely hard to form a complicated latent image simply by extending such a thick film.

In contrast, when the liquid crystalline polymer material is used, it is possible to form the latent image formation layer sufficiently thin. It is further possible to form a complicated latent image if heat and pressure are applied. For example, when a thermotropic
20 liquid crystalline polymer material is used as the liquid crystalline polymer material, an extremely complicated latent image can be formed by use of
25

a thermal head or the like. The resultant latent image is extremely stable at a temperature less than a glass transition temperature of the thermotropic liquid crystalline polymer material. Likewise, since a liquid
5 crystalline polymer material is used in the latent image formation layer in the present invention, extremely a wide range of application can be made.

In the present invention, it is necessary to arrange a light reflective surface at the rear surface
10 side of the latent image formation layer as viewed from an observer. The light reflective surface may either a surface of the optical layer having light reflectivity or one of light reflective surfaces of the light
15 reflective material. Note that the term "optical layer" used herein refers to a layer having light reflectivity such as a specular reflection layer or an OVD (Optical Variable Device) layer. Furthermore, the "light reflective substrate" includes a single-layered structure and a laminated structure of a information-
20 recorded substrate and an optical layer.

In the present invention, the optical layer is not particularly limited as long as the layer has light reflectivity, like a specular reflection layer and an OVD layer. The optical layer may have both light
25 reflectivity and light transmissivity. In the case where the optical layer is a specular reflection layer, an OVD layer may be further arranged either on the

latent image formation layer or between the specular reflection layer and the latent image formation layer.

It is preferable that a protection layer having a light transmissibility and protecting the latent image formation layer is disposed on the latent image formation layer. In particular, when the protection layer has a light scattering characteristic, it is more difficult to recognize the latent image under direct visual observation.

10 The information recording medium having the aforementioned latent image formation layer etc. can be manufactured by laminating the latent image formation layer on, for example, a light reflective substrate of a single-layered structure. Alternatively, the
15 information recording medium having the latent image formation layer etc. can be manufactured by laminating the latent image formation layer on the light reflective substrate having a laminated structure of a information-recorded substrate and an optical layer.
20 Furthermore, the information recording medium having the aforementioned information recording medium etc. may be formed by sequentially laminating the optical layer and latent image formation layer on the information-recorded substrate. Moreover, the
25 information recording medium having the aforementioned information recording medium etc. may be formed by laminating a laminated structure of the optical layer

and latent image formation layer on the information-recorded substrate. Note that the latent image may be formed in any step after the latent image formation layer is formed.

5 As mentioned above, the information recording medium can be manufactured in various methods. In most cases, employed is the method of stacking the laminated structure of the optical layer and the latent image formation layer on a information-recorded substrate.

10 When this method is employed, it is possible to use a member of imparting forgery-preventing characteristic having a laminated structure of a base layer, an optical layer, and a latent image formation layer. When such a member is used, the information recording

15 medium can be manufactured quite simply.

 The base layer used herein is preferably an adhesive layer. In this case, the member of imparting forgery-preventing characteristic can be transferred onto the information-recorded substrate by heat

20 sealing. Alternatively, a sticky layer may be attached onto the base layer at a rear side of the surface having the optical layer provided thereon. Note that the term "adhesive layer" used herein refers to the layer which requires heat for bonding, whereas the term

25 "sticky layer" used herein is the layer which is capable of bonding without heat.

 When the latent image formation layer is laminated

on the light reflective substrate of a single-layered structure or when the latent image formation layer is laminated on the light reflective substrate having a laminated structure of the information-recorded substrate and the optical layer, it is possible to employ a member of imparting forgery-preventing characteristic, which is formed by laminating the protection layer, latent image formation layer, and adhesive layer sequentially on the base layer. In this case, the base layer need to be removable from the protection layer.

It is preferable that a release layer such as a release paper or a separate paper is releasably disposed on the adhesive layer and the sticky layer.

The release layer thus disposed can prevent foreign matters from attaching onto the adhesive layer and the sticky layer before the member of imparting forgery-preventing characteristic is transferred to the information-recorded substrate. At the same time, by the presence of the release layer, the handling of the member of imparting forgery-preventing characteristic becomes easier.

In the present invention, the polarizing member may be either of a polarizing film and a polarizing board. Furthermore, a circularly polarizing member such as a circularly polarizing film can be used as the polarizing member.

Additional objects and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The objects and advantages of the invention may be realized and obtained by means of the instrumentalities and combinations particularly pointed out hereinafter.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate embodiments of the invention, and together with the general description given above and the detailed description of the embodiments given below, serve to explain the principles of the invention.

FIG. 1 is a plan view schematically showing a laminated composite according to a first embodiment of the present invention;

FIG. 2 is a cross-sectional view taken along the line II-II of the laminated composite shown in FIG. 1;

FIG. 3 is a plan view of the laminated composite shown in FIGS. 1 and 2 viewed through a polarizing film which is arranged at the side closer to an observer;

FIG. 4 is a cross-sectional view taken along the line IV-IV of the laminated composite and the polarizing film shown in FIG. 3;

FIG. 5 is a schematic view explaining the principle of the present invention;

FIG. 6 is a schematic sectional view of an information recording medium according to a first embodiment of the present invention;

FIG. 7 is a schematic plan view of an adhesive-backed sheet according to a second embodiment of the present invention;

FIG. 8 is a sectional view taken along the line VIII-VIII of the adhesive-backed sheet of FIG. 7;

FIG. 9 is a schematic view of an apparatus for use in manufacturing an information recording medium according to the second embodiment of the present invention;

FIG. 10 is a schematic sectional view of a structure obtained by using the apparatus shown in FIG. 9;

FIG. 11 is a schematic plan view of an information recording medium obtained by further adding a light-scattering protection layer to the structure shown in FIG. 10.

FIG. 12 is a sectional view taken along the line XII-XII of the information recording medium of FIG. 11;

FIG. 13 is a schematic plan view of a sheet according to a third embodiment of the present invention;

FIG. 14 is a sectional view taken along the line XIV-XIV of the sheet shown in FIG. 13;

FIG. 15 is a schematic plan view showing

a self-adhesive seal according to a fourth embodiment of the present invention;

FIG. 16 is a sectional view taken along the line XVI-XVI of the seal shown in FIG. 15;

5 FIG. 17 is a schematic sectional view of an information recording medium according to a fifth embodiment of the present invention;

10 FIG. 18 is a cross-sectional view showing a specific structure of an OVD layer of the information recording medium shown in FIG. 17;

FIG. 19 is a cross-sectional view showing a specific structure of an OVD layer of the information recording medium shown in FIG. 17;

15 FIG. 20 is a schematic sectional view of an information recording medium according to Example 6 of the present invention;

FIG. 21 is a schematic sectional view of an information recording medium according to Example 7 of the present invention; and

20 FIG. 22 is a schematic sectional view of a information recording medium according to Example 10 of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

25 The present invention will be explained more in detail with reference to the accompanying drawings. Note that the same reference numerals denote the similar structural elements and the overlapped

description is omitted.

FIG. 1 is a schematic plan view showing a laminated composite according to a first embodiment of the present invention. FIG. 2 is a cross sectional view taken along the line II-II of the laminated composite in FIG. 1.

The laminated composite 1 shown in FIGS. 1 and 2 has a laminated structure of a specular reflection layer 2 and a latent image formation layer 3. The latent image formation layer 3 contains a liquid crystalline polymer material and has an oriented portion 3a and a non-oriented portion 3b. In the oriented portion 3a, the main chains or the side chains of the polymer liquid crystal molecules are oriented in a single direction virtually parallel to the surface of the latent image formation layer 3, whereas, in the non-oriented portion 3a, the main chains and side chains of the liquid crystalline polymer molecules are not oriented. The oriented portion 3a and the non-oriented portion 3b form a latent image. When the latent image is visually observed not through a polarizing film, it is impossible or difficult to recognize the latent image.

FIG. 3 is a plan view of the laminated composite 1 shown in FIGS. 1 and 2, viewed through a polarizing film 4 arranged at the side closer to an observer. FIG. 4 is a cross-sectional view taken along the IV-IV

line of the laminated composite 1 and the polarizing film 4 shown in FIG. 3. Hereinafter, in all structures having the laminated structure of a layer having light reflectivity such as the specular reflection layer 2 and the latent image formation layer 3, the side close to the latent image formation layer 3 will be referred to as an "observer side".

When the polarizing film 4 is arranged at the observer side of the laminated composite 1, a relatively strong contrast is produced between the oriented portion 3a and the non-oriented portion 3b. As a result, the latent image is visualized. More specifically, the latent image of the laminated composite 1 can be recognized as visually observed through the polarizing film 4. This principle will be explained with reference to FIG. 5.

FIG. 5 is a schematic view for explaining the principle of the present invention. FIG. 5 shows behavior of light transmitting through the oriented portion 3a. Only the oriented portion 3a is depicted in the latent image formation layer 3. In FIG. 5, the specular reflection layer 2 forming the laminated composite 1 is drawn at a distance from the oriented portion 3a of the latent image formation layer 3. A polarizing film 4 and a light source 5 are arranged sequentially toward the observer side of the laminated composite 1.

As shown in FIG. 5, white light 6a from a light source 5, when passes through the polarizing film 4, is converted into linearly polarized light 6b. Of the linearly polarized light 6b, a light component transmitting through the oriented portion 3a of the latent image formation layer 3 is converted into elliptically polarized light 6c. The elliptically polarized light 6c is reflected by a specular reflection layer 2, passes through the oriented portion 3a, and changes to elliptically polarized light 6d. The elliptically polarized light 6d once again passes through the polarizing film 4 and changes to linearly polarized light 6e, which serves as one component of display light.

On the other hand, of the linearly polarized light 6b, a light component passing through the non-oriented portion 3b is reflected by the specular reflection layer 2 without being elliptically polarized. The linearly polarized light 6b reflected by the specular reflection layer 2 once again passes through the non-oriented portion 3b of the latent image formation layer 3 without being elliptically polarized, and further passes through the polarizing film 4.

The light component passing through the oriented portion 3a and entering the polarizing film 4 is elliptically polarized, whereas the light component passing through the non-oriented portion 3a and

entering the polarizing film 4 is linearly polarized. As a result, a relatively strong contrast is produced between the oriented portion 3a and the non-oriented portion. It is therefore possible to easily recognize a latent image.

The laminated composite 1 may be used as information recording medium.

FIG. 6 is a schematic sectional view of an information recording medium according to the first embodiment of the present invention. The information recording medium 11 shown in FIG. 6 has a laminated structure on an information-recorded substrate 13. The laminated structure is formed by sequentially laminating a specular reflection layer 2, a latent image formation layer 3, and a protection layer 14. Since such an information recording medium 11 has the laminated composite 1 mentioned above, it has a high forgery-preventing characteristics.

Now, each of the structure elements of the laminated composite 1 and the information recording medium 11 will be explained.

The information-recorded substrate 13 is a substrate for an information recording medium including credit cards, securities, and certificates, which requires to be discriminated between a genuine one and a counterfeit. Generally, some data such as letters and figures are recorded on at least one of the

main surfaces of the information-recorded substrate 13. As the information-recorded substrate 13, use may be made of a synthetic resin film such as polyethylene terephthalate, polyvinyl chloride, polyester, polycarbonate, polymethyl methacrylate or polystyrene; a natural resin film; synthetic paper; paper; or a glass plate. Furthermore, a composite formed by combining them may be used as the information-recorded substrate 13.

Various layers may be disposed on the information-recorded substrate 13. Therefore, the information-recorded substrate 13 preferably has a sufficient resistance to the processes for forming the various layers. More specifically, the information-recorded substrate 13 preferably has a sufficient strength and heat resistance. In addition, the thickness and shape of the information-recorded substrate 13 vary depending upon a final product form of the information recording medium 11, and not particularly limited.

The specular reflection layer 2 may not be particularly limited as long as it has mirror reflectivity. An evaporation film or a sputtering film made of a metal and alloy may be used. As the metal to be used in the specular reflection layer 2, there are Al, Cr, Ni, Cu, Ag and the like. As the alloy to be used in the specular reflection layer 2, there are

Pt-Rh, Ni-Cr and the like.

The latent image formation layer 3 contains a liquid crystalline polymer material. Preferably, it may consist essentially of a liquid crystalline polymer material. As the liquid crystalline polymer material, a thermotropic liquid crystalline polymer material is preferably used. More preferably, a thermotropic liquid crystalline polymer material having a glass transition temperature of about 80-200°C should be used. Examples of the thermotropic liquid crystalline polymer material include liquid crystalline polymer materials exhibiting thermotropic characteristics, such as a polyester copolymer, polyether, polycarbonate, polyisocyanate, and polyglutamate.

15 A colored layer containing a transparent color ink may be disposed between the specular reflection layer 2 and the latent image formation layer 3.

The protection layer 14 is not an essential structural element, but preferably used in the information recording medium 11. The protection layer 14 can prevent the latent image formation layer 3 from being scratched. Furthermore, the protection layer thus disposed can prevent a latent image from being viewed through traces, which are produced by heat or pressure applied at the time the latent image is formed in the latent image formation layer 3.

As the material of the protection layer 14,

a thermoplastic resin, thermosetting resin, ultraviolet or electron radiation curing resin hitherto widely used, may be employed singly or in the form of a mixture. Examples of these resins include acrylic resins, urethane-based resins, vinyl chloride resin/vinyl acetate copolymer resin, polyester-based resins, melamine-based resins, epoxy-based resins, polystyrene-based resins, polyimide-based resins, and the like.

To prevent traces from being produced by a thermal head or the like at the time a latent image is formed, the protection layer 14 may contain a curing agent for cross-linking a resin; waxes such as polyethylene wax, carnauba wax, and silicone wax; extender pigments such as calcium carbonate, zinc stearate, silica, alumina and talc; or fat and oils such as silicone oil, within the range which will not deteriorate transparency.

The protection layer 14 preferably has light scattering properties. In this case, it is possible to effectively prevent a latent image from being visually observed through the traces.

As the polarizing film 4, use may be made of a PVA-iodine type polarizing film formed by making a PVA extension film absorb an iodine, a dichroic dye type polarizing film, a metal or a metal compound containing type polarizing film, and a polymeric polycrystalline type polarizing film such as a polyen

type polarizing film. Furthermore, a circularly polarizing film may be used as the polarizing film 4. The circularly polarizing film typically used is one formed by overlaying a $1/4\lambda$ wave film over the polarizing film as mentioned above. When the circularly polarizing film is used to visualize a latent image, it is possible to observe the latent image even if the latent image is observed from any angle.

The information recording medium 11 explained above can be manufactured by the following method.

First, a specular reflection layer 2 is formed on one of the main surfaces of the information-recorded substrate 13 by an evaporation method or a sputtering method. Second, the latent image formation layer 3 is formed on the specular reflection layer 2. The latent image formation layer 3 can be formed, for example, by a known coating method such as a printing method including a gravure printing method or a screen-printing method; or a nozzle coating method. Note that the latent image formation layer 3 immediately after the formation thereof does not have a specific crystal structure. The molecules are oriented at random.

Thereafter, the protection layer 14 is formed on the latent image formation layer 3. The protection layer 14 may be formed by a printing method such as a gravure printing method, a screen printing method,

an off-set printing method or flexographic printing; or a known coating method such as a nozzle coating method.

Then, a latent image is formed on the latent image formation layer 3 of the information recording medium

5 11 on which a latent image has not yet been formed.

The formation of the latent image on the latent image formation layer 3, in other words, the formation of the oriented portion 3a and the non-oriented portion 3b can

10 be performed by applying both heat and pressure to a surface of the latent image formation layer 3 from the side of the protection layer 14. The latent image can be formed, for example, by using a hot stamp or a thermal head. Alternatively, heating by use of a laser and pressurizing by use of another apparatus
15 may be simultaneously performed. In this manner mentioned above, the information recording medium 11 shown in FIG. 6 can be obtained.

Various types of data including personal data may be recorded on the information recording medium 11 at
20 any step in the manufacturing process mentioned above. For example, after recording data on the information-recorded substrate 13, other films may be formed. Furthermore, after forming all films, data may be recorded on the information-recorded substrate 13 and
25 thereafter, a latent image may formed on the latent image formation layer 3. Furthermore, after forming all films and the latent image, data may be recorded on

the information-recorded substrate 13. Alternatively,
a part of data may be recorded on the information-
recorded substrate 13 before other films are formed,
and thereafter, the remaining data may be recorded on
5 the information-recorded substrate 13 in any one of the
steps. Data may be recorded on other structural
elements other than the information-recorded substrate
13 of the information recording medium 11.

According to the first embodiment explained above,
10 the data recording medium 11 is manufactured by
sequentially forming films on the information-recorded
substrate 13. However, the information recording
medium may be manufactured by another method.
According to second to fourth embodiments mentioned
15 below, a member of imparting forgery-preventing
characteristic may be used to manufacture the
information recording medium.

First, the second embodiment of the present
invention, which uses an adhesive-backed sheet as a
20 member of imparting forgery-preventing characteristic,
will be explained.

FIG. 7 is a schematic plan view showing
an adhesive-backed sheet according to the second
embodiment of the present invention. FIG. 8 is
25 a sectional view taken along the line VIII-VIII of the
adhesive-backed sheet shown in FIG. 7.

An adhesive-backed sheet 21 shown in FIGS. 7 and 8

has a ribbon shape. A releasable protection layer 24,
a latent image formation layer 3, and an adhesive layer
25 are sequentially laminated on one of the main
surfaces of a base layer 23. Note that the releasable
5 protection layer 24, the latent image formation layer
3, and the adhesive layer 25 constitute a heat transfer
layer 26.

FIG. 9 is a schematic view of an apparatus which
can be used in manufacturing an information recording
10 medium according to the second embodiment of the
present invention. The apparatus 31 shown in FIG. 9
has a press roll 32 and a thermal head 33. The press
roll 32 and the thermal head 33 are arranged with
a predetermined gap therebetween. The adhesive-backed
15 sheet 21 and the information-recorded substrate 13
having a specular reflection layer 2 formed thereon are
allowed to pass through the gap.

According to the second embodiment, the
information recording medium is manufactured,
20 for example, by the method mentioned below.

First, the adhesive-backed sheet 21 shown in
FIGS. 7 and 8 are prepared. The adhesive-backed sheet
21 can be obtained by sequentially forming the
releasable protection layer 24, the latent image
25 formation layer 3, and the adhesive layer 25 on one of
main surfaces of the base layer 23. On the other hand,
the information-recorded substrate 13 having the

specular reflection layer 2 on at least one of the main surfaces thereof is prepared as the light reflective substrate. Next, the light reflective substrate and the adhesive-backed sheet 21 are passed through the gap
5 between the press roll 32 and the thermal head 33 of the apparatus shown in FIG. 9 in such a manner that the specular reflection layer 2 and the adhesive layer 25 come into contact with each other. At that time, while a sufficient pressure is applied to the light
10 reflective substrate and the adhesive-backed sheet 21, the adhesive-backed sheet 21 is heated to a sufficiently high temperature with a predetermined pattern by the thermal head 33. In this manner, the heating portion of the heat transfer layer 26 is
15 transferred from the adhesive-backed sheet 21 onto the specular reflection layer 2 of the light reflective substrate.

FIG. 10 is a schematic sectional view of the structure thus obtained. As shown in FIG. 10,
20 the heat transfer layer 26 is transferred onto the specular reflection layer 2 correspondently with the aforementioned pattern. If the temperature of the hot-press transfer is sufficiently high, a latent image is formed on the latent image formation layer 3
25 of the heat transfer layer 26. More specifically, the transfer of the latent image formation layer 3 and formation of the latent image are simultaneously

performed.

When the temperature of the hot-press transfer is relatively low, only the transfer of the latent image formation layer 3 may be performed without forming a latent image. In this case, after the heat transfer layer 26 is transferred, a latent image may be formed on the latent image formation layer 3.

Note that, in this embodiment, only a heat-pressed portion of the heat transfer layer 26 is transferred as described above. Therefore, in the structure shown in FIG. 4, the transferred pattern of the heat transfer layer 26 generally coincides with that of the oriented portion, whereas the opening portion of the pattern of the heat transfer layer 26 corresponds to the non-oriented portion. The opening portion is preferably filled with a light scattering protection layer 34 as explained below.

FIG. 11 is a schematic plan view showing an information recording medium 11 obtained by further adding the light scattering protection layer 34 to the structure shown in FIG. 10. FIG. 12 is a cross sectional view taken along the line XII-XII of the information recording medium 11 shown in FIG. 11.

As shown in FIGS. 11 and 12, in the case where the light scattering protection layer 34 is provided, the surface of the resultant structure is smoothed. In this case, a latent image can be effectively

prevented from being visually observed. Furthermore, since the protection layer 34 has a light scattering characteristic, a latent image can be more effectively prevented from being visually observed. Note that, in the information recording medium 11 shown in FIGS. 11 and 12, the portion of the light scattering protection layer 34 filling the opening portion of the heat transfer layer 26 corresponds to the non-oriented portion.

Next, each of the structural elements of the adhesive-backed sheet 21 shown in FIGS. 7 and 8 and the information recording medium 11 shown in FIGS. 11 and 12 will be explained.

As the base layer 23, use may be made of a synthetic resin film such as polyethylene terephthalate, polyvinyl chloride, polyester, polycarbonate, polymethyl methacrylate or polystyrene; a natural resin film; synthetic paper; paper; a glass plate, or the like. Furthermore, a composite formed by combining them may be used as the base layer 23.

As a material for the releasable protection layer 24, use may be made of a general polymer material whose adhesive force is weaker than the adhesive layer 25 and soluble in water or an organic solvent. Examples of such a polymer material include polyvinyl alcohol, methyl cellulose, ethyl cellulose, cellulose acetate, polystyrene, polyvinyl chloride, saturated

straight-chain polyesters, methacrylic resins such as polymethyl methacrylate and polyethyl methacrylate, and copolymers thereof. Examples of the polymer material to be used in the releasable protection layer 24

5 include acrylic resins, styrene-based resins, silicone-based resins, polyisobutyl-based resins and copolymers thereof.

10 The releasable protection layer 24 can be formed by, for example, a printing method such as a gravure printing method, an off-set printing method, a screen printing method, or a known coating method such as an bar coating method, gravure method or roll coating method.

15 As a material of the adhesive layer 25, a general adhesive material may be used. Examples of such an adhesive material include a vinyl chloride/vinyl acetate copolymer; polyester-based polyamides; and adhesive agents such as acrylic resins, butyl rubber based resins, natural rubber based resins, silicone based resins, and polyisobutyl based adhesive agents. 20 If necessary, additives may be added to these adhesive agents. Examples of the additives include coagulating components such as alkyl methacrylate, vinyl ester, acrylnitrile, styrene, and a vinyl monomer; modifying components such as unsaturated carboxylic acid, 25 hydroxyl group containing monomer, and acrylnitrile; polymerizing initiation agents; plasticizers; curing

agents; accelerators; and antioxidants.

The adhesive layer 25 may be formed by a printing method such as a gravure printing method, an off-set printing method, or a screen-printing method, or a
5 known coating method such as an bar coating method, gravure method or roll coating method.

As a material of the light scattering protection layer 34, use may be made of, for example, the one which has a structure in which fine particles are
10 dissolved in a general polymer material insoluble in water or an organic solvent. Examples of such a polymer material include polyvinyl alcohol, methyl cellulose, ethyl cellulose, cellulose acetate, polystyrene, polyvinyl chloride, a saturated straight
15 chain polyester, methacrylic resins such as polymethyl methacrylate and polyethyl methacrylate, and copolymers thereof. Examples of the polymer material to be used in the light scattering protection layer 34 include acrylic resins, styrene resins, silicone resins,
20 polyisobutyl resins and copolymers thereof. Examples of the fine particles to be used in the light scattering protection layer 34 include fine particles of calcium carbonate, and silica.

The light scattering protection layer 34 can be
25 formed by a printing method such as a gravure printing method, an off-set printing method, or a screen printing method, or a known coating method such as

an bar coating method, gravure method or roll coating method.

According to the second embodiment, the adhesive-backed sheet 21 shown in FIGS. 7 and 8 is used in manufacturing the information recording medium 11 shown in FIGS. 11 and 12. An information recording medium 11 analogous to that shown in FIGS. 11 and 12 may be formed by another method. For example, first, an information-recorded substrate 13 having a specular reflection layer 2 on one of the main surfaces thereof is prepared. Second, on the specular reflection layer 2, a latent image formation layer is formed with a predetermined pattern by a gravure printing method, in place of the heat transfer layer 26. Furthermore, the protection layer 34 is formed on the latent image formation layer. Thereafter, hot-press is applied onto the protection layer 34 by a hot stamp to render the latent image formation layer in an oriented state. In this way, the information recording medium 11 analogous to that shown in FIGS. 11 and 12 can be manufactured.

According to the second embodiment, the adhesive-backed sheet 21 does not have the specular reflection layer 2, and the light reflective substrate, in which the specular reflection layer 2 is formed on the information-recorded substrate 13, is used. In contrast, a sheet having the specular reflection layer 2 is used in a third embodiment below.

FIG. 13 is a schematic plan view showing a sheet according to the third embodiment of the present invention. FIG. 14 is a sectional view taken along the line XIV-XIV of the sheet shown in FIG. 13.

5 A sheet 41 shown in FIGS. 13 and 14 has a laminated structure formed on one of the main surfaces of a base layer 43. The laminated structure is formed by sequentially laminating a specular reflection layer 2, a latent image formation layer 3, and a protection layer 14. The sheet 41 can be obtained, for example, by sequentially laminating the specular reflection layer 2, latent image formation layer 3 and the protection layer 14 on one of the main surfaces of the base layer 43. Note that the base layer 14 is an arbitral structural element and therefore may not be always formed.

10 In the sheet 41 shown in FIGS. 13 and 14, the base layer 43 has a heat-sealing property. Therefore, by laying the sheet 41 and the information-recorded substrate 13 one on the other in such a manner that the base layer 43 is in contact with the substrate 13 and pressurizing the resultant structure while heating, an information recording medium 11 analogous to that shown in FIG. 6 can be obtained. Note that, when the sheet 25 41 is used in manufacturing the information recording medium 11, the base layer 43 intervenes between the specular reflection layer 2 and the information

recording substrate 13.

It is preferable that the protection layer 14 as that explained in the first embodiment be formed on the latent image formation layer 3. The protection layer 14 thus formed can protect the latent image formation layer 3 from being scratched. Furthermore, the protection layer 14 thus formed effectively prevents visual observation of a latent image through traces, which are formed by heat and pressure applied at the time the latent image is formed on the latent image formation layer 3.

The protection layer 14 may be formed before or after the sheet 41 is adhered onto the information-recorded substrate 13. However, the protection layer 14 is usually formed before the sheet 41 is adhered onto the information-recorded substrate 13.

Now, a fourth embodiment of the present invention will be explained in which a self-adhesive seal (or a self-adhesive sticker) is employed as the member of imparting forgery-preventing characteristic.

FIG. 15 is a schematic plan view of a self-adhesive seal according to the fourth embodiment of the present invention. FIG. 16 is a sectional view taken along the line XVI-XVI of the seal shown in FIG. 15.

The self-adhesive seal 51 shown in FIGS. 15 and 16 has a structure in which the specular reflection

layer 2, the latent image formation layer 3, and the protection layer 14 are sequentially laminated on one of the main surfaces of the base layer 43, and a sticky layer 55 and a release paper 56 are
5 sequentially laminated on the other main surface of the base layer 43.

Note that the protection layer 14 and the release paper 56 are arbitral structural element in the self-adhesive seal 51. Therefore, they may not always be
10 provided.

In the self-adhesive seal 51 shown in FIGS. 15 and 16, the adhesive layer 55 is formed on the base layer 43. Therefore, by putting the self-adhesive seal 51, from which the release paper 56 is removed, onto
15 the information-recorded substrate 13 in such a manner that the adhesive layer 55 and the substrate 13 come into contact with each other, an information recording medium 11 analogous to that shown in FIG. 6 can be obtained. When the self-adhesive seal 51 is used in
20 manufacturing the information recording medium 11, the base layer 43 and the adhesive layer 55 intervenes between the specular reflection layer 2 and the information-recorded substrate 13.

It is preferable that the protection layer
25 analogous to that explained in the first embodiment is formed on the latent image formation layer 3. The protection layer thus formed can protect the latent

image formation layer 3 from being scratched. The protection layer 14 thus formed effectively prevents the visual observation of a latent image through traces formed by heat and pressure applied when a latent image is formed on the latent image formation layer 3.

The protection layer 14 may be formed before or after the self-adhesive seal 51 is put on the information-recorded substrate 13. However, the protection layer 14 is usually formed before the adhesive-backed sheet 51 is put onto the information-recorded substrate 13.

In the self-adhesive seal 51, as the material to be employed in the adhesive layer 55, use may be made of adhesives such as acrylic adhesive agent, butyl rubber-based, natural rubber-based, silicone-based and polyisobutyl-based adhesive agents. If necessary, additives may be added to these adhesive agents. Examples of the additives include coagulating components such as alkyl methacrylate, vinyl ester, acrylnitrile, styrene and a vinyl monomer; and refining components such as unsaturated carboxylic acid, a hydroxyl-group containing monomer, and acrylnitrile; polymerizing initiation agents; plasticizers; curing agents; accelerators; and antioxidants.

Although the specular reflection layer 2 is used as the optical layer in first to fourth embodiments explained above, an OVD may also be used. Note that

the OVD is, for example, a hologram or a diffraction grating capable of displaying a stereoscopic image or a special decorative image by use of light interference. Alternatively, the OVD is, for example,
5 a multi-layered film causing a color shift depending upon the observation angle.

The OVD such as a hologram or a diffraction grating is formed of a diffraction structure such as an uneven fine pattern and a band-like pattern using
10 a difference in refractivity. According to these OVDs, due to light interference and diffraction, an inherent image is emerged or a color shift is produced in accordance with the observation angle.

On the other hand, an OVD such as a multi-layered
15 thin film has a laminated structure formed by laminating ceramic layers and metal layers different in optical characteristics into multi layers. The multi-layer film uses an optical interference which varies depending upon the optical characteristics of materials
20 of the layers and the thickness of each layer. More specifically, the multi-layered film has a characteristic which reflects or transmits a light component within a specific range of wavelength. Due the characteristic, a color shift occurs depending
25 upon the observation angle.

These OVDs have a specific feature capable of displaying a stereoscopic image and causing a color

shift as explained above, so that it has an excellent decorative effect. The OVDs are therefore employed in general printing matters including wrapping materials, picture books and catalogs.

5 Note that advanced techniques are required for manufacturing these OVDs. For example, a relief-type hologram is formed as follows. To form the relief-type hologram, a relief-type master hologram with uneven-
10 form fine patterns thereon is first prepared by an optical picture-taking. Second, the uneven fine patterns are replicated from the master hologram by electroplating to form a nickel press die. Thereafter, the press die is pressed against a predetermined layer while heating. In this manner, a large number of
15 relief-type hologram replications can be obtained.

 Furthermore, a refractive hologram called a three-dimensional hologram is known. In this hologram, moiré fringes are formed in a three-dimensional manner by employing a recording material such as a photosensitive
20 resin and varying three-dimensionally the refractive index of the photosensitive resin. The hologram of this type is called as Lippmann hologram.

 Different from the hologram capable of displaying a stereoscopic image, the OVD using a diffraction
25 grating is the one which displays an image called a grating image or a pixel gram by using pixels formed of many types of simple diffraction gratings arranged

in a small area. A large number of such OVD are replicated in the same manner as in a relief-type hologram.

As mentioned above, an advanced technique is required for manufacturing the OVD. Therefore, the OVDs have been attached onto information recording mediums such as credit cards, securities, or certificates and used for preventing forgery of the mediums.

In a fifth embodiment of the present invention explained below, the OVD is used instead of the specular reflection layer 2 in the first to fourth embodiments. In this way, more advanced forgery preventing characteristics are realized.

FIG. 17 is a schematic sectional view of an information recording medium according to the fifth embodiment of the present invention. The information recording medium 61 shown in FIG. 17 has a laminated structure on the information-recorded substrate 13. The laminated structure is formed by sequentially laminating an OVD layer 62, a latent image formation layer 3, and a protection layer 14. Note that the protection layer 14 is an arbitral element, so that it is not always formed.

When the information recording medium 61 is visually observed without using the polarizing film 4, a color shift due to the OVD layer 62 is only observed

and the latent image formed on the latent image formation layer 3 cannot be recognized. In contrast, when the information recording medium 61 is visually observed through the polarizing film 4, a latent image
5 formed on the latent image formation layer 3 can be recognized.

The information recording medium 61 shown in FIG. 17 uses the OVD layer 62 having a forgery-preventing characteristic in itself in place of the
10 specular reflection layer 2. Therefore, it is more difficult to forge the information recording medium.

In the information recording medium 61, the OVD layer 62 may have various structures as mentioned above. This will be explained with reference to
15 FIGS. 18 and 19.

FIGS. 18 and 19 are cross sectional views specifically illustrating the OVD layer 62 of the information recording medium 61 shown in FIG. 17. In the information recording medium 61 shown in
20 FIG. 18, the OVD layer 62 is, for example, a relief-type hologram or a diffraction grating. In this case, a thin film made of a material with a high refractive index or a specular reflection layer 2 made of a metal is usually formed as an OVD effect layer (reflection
25 layer) 63 between the information-recorded substrate 13 and the OVD layer 62. The OVD effect layers 64 thus formed allows interference light from the OVD layer 62

to diffract with a more effective intensity. On the other hand, in the information recording medium 61 shown in FIG. 19, the OVD layer 62 is a multi-layered thin film formed by laminating thin films 65 to 67 mutually different in optical properties.

The OVD layer 62 is not particularly limited as long as it can produce an inherent image or color shift by use of light interference. The OVD layer 62 may have various structures such as a relief-type or three-dimensional-type hologram, diffraction grating, and multi-layered thin film. In consideration of mass production, the relief-type hologram (diffraction grating) or the multi-layered thin film is preferably used.

The relief type hologram can be mass-produced by a press die made of nickel, as mentioned above. More specifically, the press die is heated and pressed against a predetermined thin film to form an uneven pattern on the thin film. In this manner, a relief type hologram can be obtained. As the thin film used herein, a material, which has a good thermoformability, rarely generates nonuniform press, and gives a bright reproduction image, is preferably used. Examples of such a material include thermoplastic resins such as polycarbonate resin, polystyrene resin, and polyvinyl chloride resin; thermosetting resins such as unsaturated polyester resin, melamine resin and epoxy

resin; ultraviolet curing resin or electron radiation curing resin having a free-radical polymerizable unsaturated group, and mixtures thereof. Materials other than mentioned above may be used as long as they have sufficient properties to form the relief-type hologram.

When the OVD layer 62 is the relief-type hologram, an OVD effect layer 63 having a different refractive index from that of the OVD layer 62 is preferably provided between the OVD layer 62 and the information-recorded substrate 13. The OVD effect layer 63 thus formed improves the diffraction efficient. As a result, the latent image can be easily recognized by visual observation through the polarizing film 4.

As a material to be employed in the OVD effect layer 63, use may be made of a high refractive material such as TiO_2 , Si_2O_3 , SiO , Fe_2O_3 , or ZnS ; a metal material having a high light refractivity such as Al , Sn , Cr , Ni , Cu or Au . The OVD effect layer 63 may have a single layered structure or a laminated structure made of the aforementioned material(s). When such a material is used, the OVD effect layer 63 may be formed with a thickness of, for example, about 5 to 1000 nm by a known thin-film formation technology such as vacuum evaporation or sputtering.

Materials other than the inorganic materials mentioned above may be used in the OVD effect layer 63

as long as they have a higher refractive index (e.g., refractivity $n = 1.3$ to 1.5) or a higher light reflectivity than that of the polymer material to be used in the OVD layer 62. For example, an organic material, organic/inorganic composite material, or an inorganic filler dispersed in an organic material may be used. When such a material is used, the OVD effect layer 63 is formed with a thickness of, for example, about 0.1 to $10 \mu\text{m}$ by a known coating method or printing method such as gravure coating, die coating, or screen printing.

When the OVD layer 62 is a multi-layered thin film as shown in FIG. 19, each of the thin films 65-67 forming the OVD layer 62 may be a metal thin film, a ceramic thin film, or a composite thin film of a metal thin film and a ceramic thin film juxtaposed with each other.

When the multi-layered thin film is formed by laminating thin films different in refractivity, a thin film of a high refractivity and a thin film of low refractivity may be laminated. Alternatively, thin films of a high refractivity and thin films of low refractivity may be alternately laminated. Hence, the multi-layered thin film may have various structures. If the structure of multi-layered thin film is appropriately selected, a multi-layered thin film having desired optical properties can be obtained.

In general, a material having a refractivity of about 2.0 or more is used as the thin film of a high refractivity, whereas a material having a refractivity of about 1.5 or less is used as the thin film of a low refractivity. As a material for the thin film, a ceramic, a metal, an alloy, a polymer material, or the like may be used.

As the ceramic to be used in such a thin film, for example, use may be made of Sb_2O_3 (refractivity = 3.0: hereinafter, only numerical value is shown), Fe_2O_3 (2.7), TiO_2 (2.6), CdS (2.6), CeO_2 (2.3), ZnS (2.3), PbCl_2 (2.3), CdO (2.2), Sb_2O_3 (2.0), WO_3 (2.0), SiO (2.0), Si_2O_3 (2.5), In_2O_3 (2.0), PbO (2.6), Ta_2O_3 (2.4), ZnO (2.1), ZrO_2 (2.0), MgO (1.6), SiO_2 (1.5), MgF_2 (1.4), CeF_3 (1.6), CaF_2 (1.3-1.4), AlF_3 (1.6), Al_2O_3 (1.6), GaO (1.7) and the like.

Furthermore, the metal and alloy to be employed in the thin film may comprise Al, Fe, Mg, Zn, Au, Ag, Cr, Ni, Cu, Si and the like.

As the polymer material to be employed in the thin film, use may be made of an organic polymer such as polyethylene (1.51), polypropylene (1.49), polytetrafluoroethylene (1.35), polymethyl methacrylate (1.49), polystyrene (1.60) and the like.

The multi-layered thin film capable of absorbing or reflecting visible light having a specific wavelength can be obtained by selecting at least one of

thin films made of a high refractive material and metal thin films having a light transmissivity of 30-60%, and at least one of thin films made of a low refractive material from the thin films made of the aforementioned materials, appropriately setting each thickness of the films selected, and laminating the films alternately. For example, the multi-layered thin film can be formed by alternately laminating a thin film formed of a high-refractivity material such as ZnS, TiO₂, ZrO₂, In₂O₃, SnO, ITO, CeO₂, ZnO, Ta₂O₃, Al, Fe, Mg, Zn, Au, Ag, Cr, Ni, Cu or Si and a thin film formed of a low-refractivity material such as MgF₂, SiO₂, CaF₂, MgO, and Al₂O₃.

Note that the number of thin-film layers is 2 or more, and preferably 2-9. The spectroscopic properties of the multi-layered thin film vary depending upon the number of thin-film layers. The material for forming the multi-layered thin film may be selected based on weather-resistance, chemical-resistance, and adhesiveness in addition to optical properties such as refractivity, reflectivity, and transmissivity.

When a ceramic, metal, alloy, or the like is used in a thin film for forming the multi-layered film, a known method including a physical vapor deposition method such as vacuum evaporation or sputtering, or a chemical vapor deposition method (CVD method) may be employed. When such a method is used, it is possible

to control a film thickness, a film formation speed, the number of laminated layers or an optical film thickness ($=n \cdot d$: where n represents a refractivity and d represents a film thickness).

5 When the thin films forming the multi-layered thin film are made of a polymer material or the like, use may be made of a known method including a printing method such as gravure printing, off-set printing, or screen printing and a coating method such as
10 bar-coating, a gravure method, or a roll-coating method.

 In the information recording medium 61 according to the fifth embodiment explained above, the OVD layer 62 is provided between the information-recorded
15 substrate 13 and the latent image formation layer 3. However, when an optical layer such as the specular reflection layer 2 is formed between the latent image formation layer 3 and the information-recorded substrate 13, the OVD layer 62 may be formed on
20 the latent image formation layer 3. Furthermore, an information recording medium 61 may be manufactured by a method analogous to those explained in the first to fourth embodiments. In this case, an adhesive layer or a base layer intervenes between the latent image
25 formation layer 3 and the information-recorded substrate 13.

 Now, Examples of the present invention will be

explained.

(Example 1)

The information recording medium 11 shown in FIG. 6 was manufactured by the following method.

5 First, a metal layer of about 60 nm thick was formed as a specular reflection layer 2 by a vacuum evaporation method on one of the main surfaces of a polyethylene terephthalate (PET) substrate 13 of 50 μm thick.

10 Second, on the specular reflection layer 2, a latent image formation layer 3 was formed by a gravure method using a coating liquid for a latent-image formation layer having a composition shown below. Note that the temperature for drying was 60°C and coating thickness was 0.5 μm .

15 • Composition of the coating liquid for a latent image formation layer

Liquid crystalline polymer: 20 parts by weight
[Chiracoal PLC-7003 manufactured by Asahi Denka Kogyo K. K.]

20 MEK: 80 parts by weight

Thereafter, an FDS medium TP (manufactured by Toyo Ink Manufacturing Co., Ltd.) was print-coated, as an anchor medium, on the latent image formation layer 3 with a thickness of about 1 μm by an off-set printing method. Further, on the resultant structure, matte OP vanish 3H (manufactured by T & K Toka) was print-coated with a thickness of about 2 μm by an offset printing

25

method. As a result, a protection layer 14 was formed.

The entire latent image formation layer 3 of the information recording medium 11 manufactured in the aforementioned method was in a nonorientation state.

5 This means that a latent image was not formed in the latent image formation layer 3. Thus, the latent image was formed in the latent image formation layer 3 of the information recording medium 11 by the following method. To be more specific, heat and pressure were
10 applied to the latent image formation layer 3 by a hot stamp from the side of the protection layer 14 of the information recording medium 11, thereby forming an oriented portion 3a on the latent image formation layer 3 in a predetermined pattern. Note that the heating
15 temperature of the hot stamp was set at 120°C, and the heat/pressure was applied for 0.2 seconds.

When the information recording medium 11 having a latent image thus formed was visually observed, the latent image could not be recognized and the medium 11
20 looked as a mere metal-deposited medium. In contrast, when the information recording medium 11 was visually observed through a polarizing film 4, a latent image was visually observed as a clear image.

(Example 2)

25 An information recording medium 11 was manufactured in the same manner as Example 1 except that a latent image was formed by thermal head printing

in place of hot stamping. When the information recording medium 11 having a latent image thus formed was visually observed, the latent image could not be recognized and the medium 11 looked as a mere metal deposited medium. In contrast, when the information recording medium 11 was observed through a circularly polarizing film 4, the latent image was clearly observed as a visible image regardless of observation angle. In this example, since the latent image was formed by thermal head printing, any pattern of the latent image could be formed.

(Example 3)

The adhesive-backed sheet 21 shown in FIGS. 7 and 8 was manufactured by the following method.

An information recording medium 11 shown in FIGS. 11 and 12 was manufactured by using the sheet 21.

A releasable protection layer 24 of about 1.0 μm thick was formed on one of the major surfaces of a transparent PET base 23 of 12 μm thick by a gravure method using a coating liquid for a releasable protection layer having the composition shown below.

• Composition of the coating liquid for releasable protection layer

Acrylic resin:	20 parts by weight
----------------	--------------------

[BR-80 manufactured by Mitsubishi Rayon Co., Ltd.]	
--	--

Toluene:	40 parts by weight
----------	--------------------

MEK:	35 parts by weight
------	--------------------

Ethyl acetate: 5 parts by weight

Next, on the releasable protection layer 24,
a latent image formation layer 3 was formed by
a gravure method using a coating liquid for a latent
5 image formation layer having the composition shown
below. The temperature for drying was 60°C and the
coating thickness was 0.5 μ m.

• Composition of the coating liquid for a latent image
formation layer

10 liquid crystalline polymer: 20 parts by weight
[Kiracol PLC-7003 manufactured by Asahi Denka
Kogyo K. K.]

MEK: 80 parts by weight

Thereafter, on the latent image formation layer 3,
15 an adhesive layer 25 of 2 μ m thick was formed by
a gravure method using a coating liquid for
an adhesive layer having the composition shown below.
The adhesive-backed sheet 21 was formed as mentioned
above.

20 • Composition for the coating liquid for an adhesive
layer

Vinyl chloride/vinyl acetate copolymer:

30 parts by weight

Polyester resin:

20 parts by weight

25 MEK:

50 parts by weight

Toluene:

50 parts by weight

The adhesive-backed sheet 21 was formed on the one

hand and a specular reflection layer 2 made of Al was formed on a part of one main surface of a white PET substrate 13 having a thickness of 188 μm , on the other hand. Next, a heat transfer layer 26 constituted by the releasable protection layer 24, the latent image formation layer 3 and the adhesive layer 25 was transferred onto the specular reflection layer 2 in a predetermined pattern from the adhesive-backed sheet 21 by an apparatus 31 shown in FIG. 9. As a result, the structure shown in FIG. 10 was obtained. Note that the heating temperature by the thermal head 33 was 120°C and the heat/pressure was applied for 0.2 seconds. The entire heat transfer layer 26 on the specular reflection layer 2 was in an orientation state and had a latent image formed thereon.

Next, an FDS medium TP (manufactured by Toyo Ink Manufacturing Co., Ltd.) was print-coated, as an anchor medium, on the specular reflection layer 2 with a thickness of about 1 μm by an off-set printing method. Further, on the resultant structure, matte OP vanish 3H (manufactured by T & K Toka) was print-coated with a thickness of about 2 μm to obtain a light-scattering protection layer 14 of about 3 μm . In the way, the information recording medium 11 shown in FIGS. 11 and 12 was manufactured.

When the information recording medium 11 was visually observed, a latent image was not recognized

and the medium 11 looked as a mere medium with
a light-reflective seal partly provided on the surface.
In contrast, when the information recording medium 11
was visually observed through the polarizing film 4,
5 the latent image was clearly observed as a visible
image.

(Example 4)

The self-adhesive seal 51 shown in FIGS. 15 and 16
was manufactured by the following method.

10 First, a metal film of about 60 nm thick was
formed as a specular reflection layer 2 on one of the
main surfaces of a PET base 43 of 50 μm thick by
a vacuum evaporation method. Second, on the specular
reflection layer 2, a latent image formation layer 3
15 was formed by a gravure method using a coating liquid
for a latent image formation layer having the
composition shown below. Note that the temperature for
drying was 60°C and the coating thickness was 0.5 μm .

• Composition of a coating liquid for a latent image
20 formation layer

Liquid crystalline polymer: 20 parts by weight
[Kiracol PLC-7003 manufactured by Asahi Denka
Kogyo K. K.]

MEK: 80 parts by weight

25 Thereafter, on the latent image formation layer 3,
an FDS medium TP (manufactured by Toyo Ink
Manufacturing Co., Ltd.) was print-coated as an anchor

medium with a thickness of about 1 μm by an off-set printing method. Further, on the resultant structure, matte OP vanish 3H (manufactured by T & K Toka) was print-coated as a top coating vanish with a thickness of about 2 μm to obtain a light-scattering protection layer 14 of about 3 μm . Subsequently, an adhesive layer 55 was formed on the other surface of the PET base 43.

The entire latent image formation layer 3 of the self-adhesive seal 51 manufactured in the method mentioned above was in a nonorientation state. This means that a latent image was not formed on the latent image formation layer 3. Thus, a latent image was formed on the latent image formation layer 3 of the self-adhesive seal 51 by the following method. More specifically, heat/pressure was applied by a hot stamp to the latent image formation layer at a side of the protection layer 14 of the self-adhesive seal 51, thereby forming an oriented portion 3a on the latent image formation layer 3 in a predetermined pattern. The heating temperature by the hot stamp was set at 120°C and heat/pressure was applied for 0.2 seconds.

When the self-adhesive seal 51 having the latent image thus formed was visually observed, the latent image was not recognized and the seal 51 looked as a mere metal-deposited self-adhesive seal. In contrast, when the self-adhesive seal 51 was visually observed

through a polarizing filter 4, a latent image was clearly observed as a visible image.

(Example 5)

An self-adhesive seal 51 was manufactured in the same manner as in Example 4 except that a latent image was formed by thermal head printing in place of a hot stamp. When the self-adhesive seal 51 having the latent image formed thereon was visually observed, the latent image was not recognized and the seal 51 looked as a mere metal deposited self-adhesive seal. In contrast, when the self-adhesive seal 51 was visually observed through a circularly polarizing film 4, the latent image was clearly observed as a visible image regardless of observation angle. In this Example, since the latent image was formed by thermal head printing, any pattern of the latent image could be formed.

(Example 6)

FIG. 20 is a schematic sectional view of an information recording medium 71 according to Example 6 of the present invention. The information recording medium 71 was manufactured by the following method.

An Al thin film of 60 nm thick was formed as a specular reflection layer 2 by an evaporation deposition method on one of the main surfaces of a card substrate 13 made of vinyl chloride and having a thickness of 780 μ m. Subsequently, a rainbow hologram

pattern 72 was formed by a roll emboss method, i.e., by pressing a stamper of a relief type rainbow hologram heated to 140°C against the surface of the card substrate 13 having the specular reflection layer 2 formed thereon. That is, an OVD layer was formed on one of the main surfaces of the card substrate 13.

Subsequently, a latent image formation layer 3 was formed on the rainbow hologram pattern 72 by a gravure method using a coating liquid for the latent image formation layer having the composition shown below. Note that the temperature for drying was 80°C and coating thickness was 1.0 μm .

• Composition of a coating liquid for a latent image formation layer

15 Liquid crystalline polymer: 20 parts by weight
 [Kiracol PLC-7003 manufactured by Asahi Denka
Kogyo K. K.]

MEK: 80 parts by weight

Thereafter, the coating liquid for protection layer having the composition shown below was coated as a UV curing resin with a thickness of 2.5 μm on the latent image formation layer 3. The coating film was cured by a UV radiation machine to form a protecting film 14.

25 • Composition of a coating liquid for a protection layer

Urethane acrylate: 60 parts by weight

Radical polymerization initiator:

3 parts by weight

Methylethyl ketone:

37 parts by weight

5 The entire latent image formation layer 3 of the
information recording medium 71 manufactured by the
aforementioned method was in a non-orientation state.
This means that a latent image was not formed on the
latent image formation layer 3. Thus, a latent image
was formed on the latent image formation layer 3 of the
10 information recording medium 71 by the following
method. To explain more specifically, heat/pressure
was applied by a hot stamp to the latent image
formation layer at a side of the protection layer 14 of
the information recording medium 71, thereby forming an
15 oriented portion 3a on the latent image formation layer
with a predetermined pattern. The heating temperature
by the hot stamp was set at 120°C and the heat/pressure
was applied for 0.2 seconds. As the hot stamp, a
printing board having a projection of a letter string
20 "TOP" formed thereon was used.

The information recording medium 71 having a
latent image thus formed was visually observed.
However, the latent image was not recognized and the
medium 71 looked as a mere OVD medium. In contrast,
25 when the information recording medium 71 was visually
observed through a circularly polarizing film 4, the
letter string was clearly observed as a visible image.

(Example 7)

FIG. 21 is a schematic sectional view of the information recording medium 81 according to a seventh embodiment of the present invention. In this example, the information recording medium 81 was manufactured by the method shown below.

First, as the OVD layer 62, a commercially available hologram transfer foil 62 was transferred by a hot stamp to a part of one main surface of the card substrate 13 made of vinyl chloride and having a thickness of 780 μm . Second, a latent image formation layer 3 was formed on the OVD layer 62 by a gravure method using a coating liquid for the latent image formation layer having the composition shown below. The temperature for drying was 80°C and the coating thickness was 1.0 μm .

• Composition of the coating liquid for a latent image formation layer

Liquid crystalline polymer: 20 parts by weight
[Kiracoal PLC-7003 manufactured by Asahi Denka Kogyo K. K.]

MEK: 80 parts by weight

Thereafter, a coating liquid for the protection layer having the composition shown below was coated as a UV curing resin on the latent image formation layer 3 with a thickness of 2.5 μm . The coating film was further cured by a UV radiation machine to form a

protecting film 14.

• Composition of a coating liquid for a protection layer

Urethane acrylate: 60 parts by weight

5 Radical polymerization initiator:

3 parts by weight

Methylethyl ketone: 37 parts by weight

10 The entire latent image formation layer 3 of the information recording medium 81 manufactured by the aforementioned method was in a non-orientation state. This means that a latent image was not formed on the latent image formation layer 3. Thus, a latent image was formed on the latent image formation layer 3 of the information recording medium 81 by the following method. To explain more specifically, heat/pressure was applied by a hot stamp to the latent image formation layer 3 at a side close to the protection layer 14 of the information recording medium 81, thereby forming an oriented portion 3a on the latent image formation layer 3 in a predetermined pattern. The heating temperature by the hot stamp was set at 120°C and the heat/pressure was applied for 0.2 seconds. As the hot stamp, a printing board having a projection of a letter string "TOP" formed thereon was used.

15

20

25

The information recording medium 81 having a latent image thus formed was visually observed.

However, the latent image was not recognized and the medium 81 looked as a mere OVD medium. In contrast, when the information recording medium 81 was visually observed through a circularly polarizing film 4, the letter string was clearly observed as a visible image.

Examples 1-7 demonstrate that extremely high forgery-preventing characteristic can be attained by using a liquid crystalline polymer material. In other words, the latent image which cannot be visually recognized by a simple observation but clearly observed as an extremely visible image through a polarizing film can be easily formed in a desirable pattern.

In contrast, when a liquid crystalline polymer material is not used, all of these effects are not always obtained. For example, when a thin film formed of a polymeric material such as polypropylene, polyethylene, polystyrene or polyester is used as the latent image formation layer 3, a latent image may be formed by scratching or scrubbing a surface of the thin film with a brush, sandpaper, or sandblast.

Furthermore, the latent image formation layer 3 may be formed by pulverizing the thin film in an orientation state into small pieces, dispersing the small pieces into a polymer resin such as polyester or acryl and applying the dispersion solution thus obtained. However, the pattern of the latent image obtained is generally random. This means that, by

this method, formation of a latent image with a predetermined pattern is difficult.

Examples 8 to 10 are concerned with a method of attaining forgery-preventing characteristics without using the liquid crystalline polymer material.

(Example 8)

An Al light reflection layer of about 60 nm thick was formed by a vacuum evaporation method on one of the main surfaces of a polypropylene sheet of 50 μ m thick. A surface of the light reflection layer was scrubbed by a nylon brush in a single direction. In this manner, the entire surface was polarized.

Subsequently, a part of the surface of the light reflection layer was masked with an acrylic resin by a screen-printing method. Furthermore, the surface of the light reflection layer was scrubbed by a nylon brush in the direction perpendicular to the direction mentioned above. As a result, the exposed portion of the surface of the light reflection layer lost the polarization characteristic. In this way, a latent image was formed on the surface of the light reflection layer. Thereafter, an acrylic resin was removed from the sheet to thereby obtain a sheet having a forgery-preventing characteristic.

When the sheet thus manufactured was visually observed, a latent image was not recognized and the sheet looked as a mere metal deposited sheet.

In contrast, when the sheet was visually observed through a polarizing film, the latent image was clearly observed as a visible image.

(Example 9)

5 The sheet having a forgery-preventing characteristic formed in Example 8 was laminated on one of the main surfaces of a PET film of 100 μ m thick in such a manner that its light reflection layer was in contact with the PET film. Then, an ultraviolet curing
10 ink was coated (applied) to the surface of the light reflection layer having a latent image formed thereon by off-set printing. The coated (applied) film was cured by a UV lamp to form a protection film. The information recording medium was manufactured in this
15 manner.

When the medium thus manufactured was visually observed, the latent image was not recognized and the medium looked as a mere metal deposited medium. In contrast, when the medium was visually observed through
20 a circularly polarizing film, the latent image was observed as a visible image.

(Example 10)

FIG. 22 is a schematic sectional view of an information recording medium 91 according to
25 Example 10. In this example, the information recording medium 91 was manufactured by the method shown below.

First, an Al film 65, SiO₂ film 66, and an Al

film 67 were sequentially formed on one of the main surfaces of the card substrate 13 having a thickness of 780 μm and made of vinyl chloride by a vacuum evaporation method. As a result, a multi-layered thin film 62 was obtained. Note that the thicknesses of the Al film 65, SiO_2 film 65 and the Al film 67 are 70 nm, 580 nm, and 20 nm, respectively.

On the other hand, the letter string "TOP" was formed as a latent image by a rubbing method on one of the main surfaces of polypropylene film 93 of 100 μm thick, which is formed by a protrusion molding method. More specifically, an oriented portion 93a and a non-oriented portion 93b were formed in the polypropylene film 93. Subsequently, a heat sensitive adhesive layer 94 of 2 μm thick was formed by a gravure method using an adhesive-layer coating liquid having the composition shown below on the rear surface with respect to the surface of the film 93 having the latent image formed thereon.

•Composition of the adhesion-layer coating liquid

Olefin-based heat sensitive adhesive:

15 parts by weight

Toluene:

85 parts by weight

Furthermore, the film 93 and the card substrate 13 were put one on the other in such a manner that the multi-layered thin film 62 was in contact with the adhesion layer 94. The resultant structure was heated

to 80°C while pressurizing it, to adhere them. In the manner mentioned, the information recording medium 91 was obtained.

When the information recording medium 91 was visually observed, a latent image was not visually recognized and the medium 91 looked as a mere OVD medium. In contrast, when the medium 91 was visually observed through a circularly polarizing film, the latent image was visually observed as a visible image.

As explained in the above, in the present invention, an oriented portion and a non-oriented portion are formed in the latent image formation layer. These portions form a latent image. The latent image can not be recognized under direct visual observation, but can be recognized under visual observation through a polarizing member. More specifically, according to the present invention, the visualization and non-visualization of the latent image can be performed repeatedly. In addition, discrimination of a medium between a genuine one and a counterfeit is easily performed without using a large-scale apparatus for visualizing the latent image.

According to the present invention, the oriented portion and non-oriented portion of the latent image formation layer are made of a liquid crystalline polymer material. It is therefore possible to easily form a complicated latent image having a sufficient

resistance.

Furthermore, in the present invention, the oriented portion and non-oriented portion are made of the liquid crystalline polymer material. It is therefore possible to form a latent image formation layer extremely thin. Hence, the forgery preventing technique of the present invention can be applied to any types of information recording mediums.

Simultaneously, forgery-preventing characteristic can be imparted to an information recording medium in various ways.

More specifically, according to the present invention, there is provided a forgery-preventing technique which is capable of repeating the visualization and nonvisualization of a latent image, forming a complicated latent image having a sufficient resistance, and easily discriminating a medium between a genuine one and a counterfeit, and which does not require a large apparatus for visualizing the latent image. Furthermore, according to the present invention, there is provided a laminated composite capable of being used in the forgery-preventing technique, an information recording medium having a forgery-preventing characteristic imparted thereto by such a forgery-preventing technique, and a member of imparting the forgery-preventing characteristic to an information recording medium by using such

a forgery-preventing technique.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to
5 the specific details and representative embodiments shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.

5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
221